

10/588645

AP20 Rec'd PCT/PTO 07 AUG 2006

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application No. : Confirmation No. :
First Named Inventor : Uwe LIMBECK
Filed : August 7, 2006
TC/A.U. :
Examiner :

Docket No. : 102063.56866US
Customer No. : 23911

Title : Method to Cold-Start Fuel Cell System at Sub-Zero
Temperatures

SUBMISSION OF SUBSTITUTE SPECIFICATION


Mail Stop PCT
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

August 7, 2006

Sir:

Attached are a Substitute Specification and a marked-up copy of the original specification. I certify that said substitute specification contains no new matter and includes the changes indicated in the marked-up copy of the original specification.

Respectfully submitted,



Gary R. Edwards
Registration No. 31,824

CROWELL & MORING LLP
Intellectual Property Group
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844
GRE:kms
2822836_1

METHOD TO COLD-START A FUEL CELL SYSTEM AT SUB-ZERO
TEMPERATURES

[0001] This application claims the priority of German patent document 10 203 029.4, filed February 6, 2004 (PCT International Application PCT/US2005/003357, filed February 4, 2005), the disclosure of which is expressly incorporated by reference herein.

[0002] The present invention concerns a method to cold-start a fuel cell system at sub-zero temperatures.

BACKGROUND OF THE INVENTION

[0003] One general problem of fuel cell systems is their start-up at low temperatures, *i.e.*, at temperatures significantly below 0°C. For example, if a fuel cell system is to be started at a temperature of -15°C, one first uses a heating device associated with the fuel cell system to heat the fuel cell system (in particular its stack of membrane-electrode assemblies) to a temperature of, for example, +5°C, and only then starts the fuel cell system. This is based on the consideration that the fuel cell system must first be heated to a temperature above which the water generated by the fuel cell system can no longer freeze, since freezing would create problems. The heating device may comprise a burner to generate the required thermal energy, whereby the burner may, for example, be operated with hydrogen that is also used as fuel for the fuel cell system. The

heat generated by the burner may be used to heat a cooling fluid, which circulates in a coolant loop that serves to cool the fuel cell stack during the subsequent operation of the fuel cell stack. The coolant heated by the burner of the heating device circulates in the coolant loop and in this manner transfers the thermal energy to the fuel cell stack to preheat the fuel cell stack.

[0004] The above-described pre-heating process must be completed in as short a time period as possible, so that the fuel cell system can be started as quickly as possible, even at low ambient temperatures. During this pre-heating process, a significant amount of heat has to be transferred to the coolant in a short time period. This in turn means that a corresponding air flow has to be supplied to the burner, which can be accomplished only with the help of a powerful fan or a compressor. For this reason, the overall electrical power required prior to the actual start of the fuel cell system is very high, since it is necessary to operate not only the above-mentioned fan or compressor, but also the coolant circulating pump and a control unit that controls the heating process. Since normally the fuel cell stack does not generate any power during the heating process, the required electrical power is generally provided by a correspondingly large battery. This is undesirable for weight- and space-related reasons, in particular for mobile fuel cell applications.

SUMMARY OF THE INVENTION

[0005] One objective of the invention is to provide an improved method for the cold-starting of a fuel cell system with lower battery energy requirements.

[0006] This and other objects and advantages are achieved by the method according to the invention, which starts a fuel cell system with a fuel cell stack and a heating device connected upstream of the fuel cell stack to heat a cooling agent to be circulated by a coolant pump. The cold fuel cell stack is operated at a capacity that generates enough power to operate the heating device and the coolant pump. The power generated by the fuel cell is used to operate the heating device for heating the coolant and the coolant pump for circulating the coolant between the fuel cell stack and the heating device; and the heating device is switched off as soon as the fuel cell stack has reached a present temperature that is higher than the original temperature.

[0007] The invention is based on the capability of a fuel cell system to run at sub-zero temperatures, at least under low load conditions and for a short period of time. It has been known that fuel cell systems can generate power at sub-zero temperatures (*see, e.g.*, U.S. Patent No. 5,798,186), but it is also known that prolonged operation at sub-zero temperatures can lead to problems, such as ice formation in the lines for the reactant streams. For this reason, it was widely assumed that the fuel cell stack itself is not really suitable as a power source during the cold-start of a fuel cell system. In contrast, it has been found that even under such conditions, the fuel cell stack is able to deliver an amount of

power that is at least sufficiently large to operate the heating device, preferably even to operate the coolant pump and an air compressor. An important factor is the fact that the fuel cell stack can provide this amount of power over a time period that is long enough to heat it to a temperature above zero before ice formation sets in. Thus, a battery or other energy source is needed only for the actual starting of the fuel cell system, and the battery can be much smaller than conventionally thought, since immediately after the below-zero start-up of the fuel cell stack, the fuel cell stack will provide power.

[0008] Preferably, the method according to the invention is implemented in such a way that the fuel cell system will be operated at a capacity that is just barely sufficient to provide the power necessary to operate the heating device, the coolant pump, and possibly necessary auxiliaries.

[0009] A further advantage of the method according to the invention is that the fuel cell stack generates heat immediately after its start-up at sub-zero temperatures, which results in more rapid heating, and thus a shorter waiting period before the fuel cell system can provide full power.

[0010] Even an interruption of the start-up process, which usually takes approximately one minute, is no problem for the invention, since according to the invention the cold fuel stack can be operated at low load for a duration of several minutes, which allows three to four successive start-up processes using the method according to the invention.

[0011] In one embodiment of the method according to the invention, the preset temperature is +5°C (*i.e.*, the heating device of the fuel cell system is switched off when the fuel cell stack has reached a temperature of +5°C). But it should be understood that other preset temperatures can be used according to the invention, if they are sufficiently high to allow the fuel cell system to reach its operating temperature without additional external heat input. The present assumption in this regard is that for fuel cell systems with solid polymer electrolytes these preset temperatures must be above the freezing point, preferably close to or above +5°C.

[0012] In preferred embodiments of the method according to the invention, the heating device is a burner. This burner may, for example, be fuelled with hydrogen, which is advantageous since the fuel cell stack also requires hydrogen for its operation. If the heating device is a burner, then the process of operating the cold fuel cell stack at low load to generate the required power is implemented so that sufficient power is generated to operate the auxiliaries necessary for the operation of the burner (starting device of the burner, fan or compressor for air supply, etc.). Of course, there also has to be sufficient power to operate the coolant pump.

[0013] The method according to the invention can realize cost advantages if a burner serves as the heating device, since neither the burner nor the heat exchanger (or heat exchangers) needs be rigorously designed for the lowest possible pressure loss, as has been the case traditionally in order to keep the electrical power needed to operate the heating device prior to the actual start-up

of the fuel cell system as low as possible. For this reason, according to the invention, both the burner and the heat exchanger (or heat exchangers) can be smaller and thus less expensive and more compact.

[0014] If a burner serves as the heating device, the method according to the invention can realize further advantages by employing one and the same air compressor to supply both the fuel cell stack and the burner with oxygen. This reduces the power requirements even further.

[0015] If in the method according to the invention one employs one and the same air compressor to supply air to both the burner and the fuel cell stack, then the air volume delivered by the air compressor may be divided between the burner and the fuel cell in a ratio that favors the burner. In one embodiment, this ratio is 4:1.

[0016] One may use a high-performance gas burner as the burner for the method according to the invention. Such a high-performance gas burner can deliver in a short amount of time the significant amount of heat that has to be transferred to the cooling agent. In one embodiment, the high-performance gas burner has a power output in a range of approximately 30 kW to 90 kW. Depending on the desired burner output, a burner of this type requires an air mass flow rate of between approximately 50 kg/hr and 300 kg/hr during operation. As mentioned before, hydrogen may be used to operate the burner.

[0017] Thus the present invention overall provides a significantly improved method for cold-starting a fuel cell system at sub-zero temperatures, in

which the desired short “start-up times” can be achieved despite the lower battery-power requirements and lower space requirements for the smaller components. As used herein, the term “start-up time” refers to the time required for the fuel cell stack of a cold fuel cell system to be able to deliver its full power.

[0018] Other objects, advantages and novel features of the present invention will become apparent from the following detailed description of the invention when considered in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] The single Figure illustrates a fuel cell stack with a heating device that is connected upstream thereof or integrated therein.

DETAILED DESCRIPTION OF THE INVENTION

[0020] Referring to the Figure, a fuel cell stack 10 with one anode 12 and one cathode 14 are disclosed. Hydrogen is supplied to the anode 12 from a source (not shown) via a line 6. Via a line 18, the cathode 14 is supplied with oxygen in the form of air, which has been compressed by a compressor 20. During its operation, the fuel cell stack 10 uses the supplied hydrogen and oxygen to produce power and water in a manner which is known in the art (and therefore will not be explained in more detail).

[0021] For the purpose of cooling the fuel cell stack 10 during its operation, it is connected in a heat-exchanging manner to a cooling loop 22, which includes

a heat exchanger 23 in the form of a radiator, to dissipate the excess heat that is produced during the operation of the fuel cell stack 10. The cooling loop 22 also has a heat-exchanging connection to a heating device 24, which supplies heat to the cooling agent circulating in the cooling loop 22 during the start-up phase, so that the fuel cell stack 10 can be heated more rapidly to operating temperature from very low ambient temperatures.

[0022] In the illustrated embodiment, the heating device 24 comprises a high-performance gas burner 26 that is operated with hydrogen and produces hot gas, whereby an additional heat exchanger 28 is used to transfer the thermal energy of the hot gas to the cooling agent circulating in the cooling loop 22. The gas burner 26 is supplied with hydrogen via a line 30, which branches off the line 16. In a mixer 32 upstream of the gas burner 26, hydrogen is mixed with the particular volume of air (delivered by the compressor 20 via line 18) that is necessary to achieve proper combustion. Control valves 34 and 36 effect the desired distribution of the hydrogen flow and the air flow between the fuel cell stack 10 and the gas burner 26 or mixer 32. In a preferred embodiment of the invention, the air volume is divided between the burner and the fuel cell stack with a ratio that favors the burner; for example, a ratio of 4:1.

[0023] A coolant pump 38 circulates the cooling agent through the cooling loop 22. As shown in the Figure, the cooling loop 22 typically is a closed loop. In the shown embodiment example, the heat exchanger 23 used to cool the cooling agent during operation is separate from the heat exchanger 28 that is used to heat the cooling agent during the start-up phase, but it is also possible for the

heat exchangers 23 and 28 to employ common components or to be integrated into each other.

[0024] The illustrated arrangement operates as follows. At first the compressor 20 is started with the help of a battery (not shown) and the hydrogen supply via the line 16 is opened, so that air and hydrogen are fed to the fuel cell stack 10. The fuel cell stack 10 commences operation and is set by its control system to operate at low load, *e.g.*, at approximately 10% of its rated power. The power generated by the fuel cell stack 10 is now used to drive the compressor 20, the coolant pump 38, and all auxiliaries necessary for the operation of the heating device 24 and the fuel cell stack 10. The heating device 24 (in particular, its gas burner 26) is started and the hot gas generated by its heats the cooling agent in the cooling loop 22, which is circulated through the cooling loop 22 by the coolant pump 38. In this operating state, the heat exchanger 23 is not operating. (That is, either it is not supplied with cooling agent or the cooling agent circulating in the cooling loop 22 is carried past the heat exchanger 23, for example, by means of a bypass line (not shown) that bypasses the heat exchanger 23.

[0025] As soon as the fuel cell stack 10 has reached the temperature required for normal operation (for example, +5°C), the gas burner 26 is switched off and the fuel cell stack 10 can be operated at a higher load, or at full load, if required. In this operating state the cooling loop 22 serves its actual purpose, namely cooling the fuel cell stack 10 by means of the heat exchanger 23.

[0026] The following is an example of the application of the method of the present invention in a fuel cell system which includes a polymer-electrolyte-membrane fuel cell stack with an output power of approximately 85 kW. This fuel cell stack can be operated for approximately 3 to 4 minutes at -15°C and at a load of approximately 5% to 10% of its nominal output power (*i.e.*, with an output power of approximately 4 to 7 kW), before problems occur due to ice formation or similar factors.

[0027] According to the method of the invention, the fuel cell system needs only a quantity of heat sufficient to heat the fuel cell stack from -15°C to a temperature from which it can reach its operating temperature on its own, without outside help. In the fuel cell systems in this example, this temperature was assumed to be +5°C. to be able to carry out three to four subsequent start-up processes in rapid succession, each of the start-up processes has to be completed in less than approximately 1 minute.

[0028] To heat the fuel cell stack from -15°C to +5°C, it is necessary to introduce a computed quantity of heat between 1800 and 2200 kJ into the cooling agent. It is desirable to transfer this amount of heat to the cooling agent within approximately 40 seconds, so that during the remaining 20 seconds the cooling agent can transfer the absorbed heat to the actual fuel cell stack. The listed requirements translate into a power of approximately 45 to 55 kW, which the burner must be able to generate and the heat exchanger must be able to transfer. For the burner to generate this quantity of heat, approximately 20 kg/hr of air has to be carried to the burner and subsequently to the heat exchanger.

Assuming that an additional 3 to 50 kg/hr of air has to be supplied to the fuel cell stack during the same time period in order for the fuel cells tack to generate the required electrical power, the compressor must be able to deliver a flow of approximately 230 to 250 kg/hr during the start-up process. Dependent on the pressure gradient that the compressor has to produce, this corresponds to approximately 2 to 5 kW of electrical power that must be supplied to the compressor. Added to this must be the electrical power of approximately 800 W required by the coolant pump and the approximately 500 W that is needed by additional loads, such as sensors, control systems, etc., so that the fuel cell stack has to generate approximately 3 ½ to 6 ½ kW of electrical power during the start-up process.

[0029] As explained above, the fuel cell stack is able to generate an output power of this level already during the start-up process, which makes it possible to use a smaller starter battery. A starter battery that needs only to be able to start the fuel cell stack requires an output power of not more than 1.5 kW for less than 5 seconds, whereas a battery that must also provide power during a cold-start process has to be able to provide a power output of at least approximately 6 kW for up to 60 seconds. A 1.5 kW battery is significantly smaller and less expensive than a 6 kW battery, and further evidences an advantage of this invention.

[0030] The foregoing disclosure has been set forth merely to illustrate the invention and is not intended to be limiting. Since modifications of the disclosed embodiments incorporating the spirit and substance of the invention may occur

to persons skilled in the art, the invention should be construed to include everything within the scope of the appended claims and equivalents thereof.